

INDEX OF AUTHORS

VOLUME XLVI

TRANSACTIONS OF AMERICAN SOCIETY FOR METALS

1954

A

Allten, A. G. 948
Armiento, D. F. 1500
Averbach, B. L. 851

B

Backofen, W. A. 655
Bailey, E. F. 830
Barnett, W. J. 1557
Bechtold, J. H. 397, 1449
Bever, M. B. 1359
Birtalan, John 928
Bishop, H. F. 418
Breen, J. E. 1021
Brick, R. M. 973, 1406
Brown, W. F., Jr. 998
Busby, C. C. 100
Busby, Paul E. 1331

C

Carlson, R. G. 483
Carman, C. M. 1500
Carney, D. J. 882
Chalmers, B. 1214
Chambers, D. S. 759
Chang, J. C. 1298
Chow, J. G. Y. 948
Christenson, A. L. 928
Clark, C. L. 1285
Clark, D. S. 34
Cohen, Morris 727, 851
Corbett, R. B. 1599
Crouse, C. S. 716

D

DeLazaro, D. J. 292
Doig, J. R. 231, 1056
Dorn, J. E. 113, 348, 681, 1075
Dotson, C. L. 1470
Dulis, E. J. 1318

E

Ebeling, D. G. 799
Ellis, W. E. 1039

F

Feduska, A. 1599
Feuerstein, W. J. 1270
Fischer, R. B. 329
Fishel, W. P. 277
Fleischmann, Martin 1039
Floer, C. F. 1359
Frerichs, R. C. 1285
Frohberg, R. P. 1557
Frost, P. D. 231, 257, 568, 1056

G

Goldberg, Alfred 681
Grange, R. A. 446
Grant, N. J. 540
Griest, A. J. 257
Griffith, C. B. 375
Grobe, A. H. 759
Grosse, A. V. 525

H

Hammond, J. P. 716
Hansen, M. 354, 587, 609
Hazlett, T. H. 701
Henley, R. G., Jr. 928
Hirsch, L. L. 231, 1056
Hull, F. C. 87
Hultgren, Ralph 1298
Hundy, B. B. 655

J

Jackson, J. H. 157, 257, 329, 568

K

Kessler, H. D. 587, 609
Kiefer, G. C. 197
Kirshenbaum, A. D. 525
Klingler, L. J. 1557
Kula, Eric 727

L

LaChance, M. H. 157
Lane, J. R. 1021

Larson, F. R.	1377	Rinebolt, J. A.	1527
Lement, B. S.	851	Ripling, E. J.	184
Lena, A. J.	197	Roach, D. B.	329
Leslie, W. C.	1470	Roberts, G. A.	759
Lillys, Peter	1176	Rosenberg, S. J.	1225
Loria, E. A.	409	Rostoker, W.	292, 1136
Lownie, W. H., Jr.	409	Russell, J. V.	129
Lucas, W. R.	277		
Lula, R. A.	197		

M

Mallett, M. W.	375, 640
Margolin, H.	312
Markus, Harold	1500
McBride, C. C.	499
McHargue, C. J.	716
McMullin, J. G.	799
McPherson, D. J.	354
Meyerson, M. R.	1225
Millar, D. A. J.	1544
Mitchell, J. B.	446
Moorhead, P. E.	257
Mossman, R. A.	525

N

Nehrenberg, A. E.	1176
Nielsen, J. P.	312

O

Olleman, R. D.	87
Orr, R. L.	113
Owen, W. S.	812

P

Palty, A. E.	312
Parker, E. R.	701
Parris, W. M.	231, 568, 1056
Pellini, W. S.	418
Peretti, E. A.	389
Phillips, C. W.	63
Poole, S. W.	129
Powell, G. W.	1359
Powers, A. E.	483

R

Ransom, J. T.	1254
Reiter, S. F.	799
Rickett, R. L.	1470

S

Salmas, J.	1377
Sandoz, G.	418
Sawyer, C. F.	100
Schwartz, C. M.	231, 640, 1056
Schwartzbart, Harry	998
Shaler, A. J.	655
Shaw, R. B.	1075
Sherby, O. D.	113, 681
Shewmon, P. G.	397
Shih, C.	389
Simon, A.	948
Sinnott, M. J.	63
Smith, G. V.	1318
Smith, R. L.	973
Smith, W. K.	1270
Spangler, G.	973
Speiser, Rudolph ...	499, 1089, 1168
Spretnak, J. W.	499, 1089, 1168
Starr, C. D.	348, 1075
Steijn, R. P.	1406
Succop, J. A.	1599

T

Taylor, W. J.	1168
Troiano, A. R.	1557

V

Vajda, John	1331
------------------	------

W

Walton, C. S.	1470
Wells, Cyril	129
Wessel, E. T.	87
Winegard, W. C.	1214
Wulff, John	1544
Wyatt, J. L.	540

Y

Yamamoto, A.	1136
-------------------	------

SUBJECT INDEX

Activation energy

- for creep correlation with
rupture and self-diffusion
data125-127
- diffusion of carbon in
austenite 826
- effect of silicon 826
- diffusion of carbon in
ferrite 826
- effect of silicon 826

Activation energy for rupture

- of aluminum 118
- of beryllium 120
- of molybdenum 122
- of nickel 121
- of niobium 121

A-Embrittlement874-875

Age hardening

- alpha-molybdenum die
steels1608-1612
- of titanium alloys
effect on properties ...576-584
- titanium-aluminum-chromium
alloys620-622, 637-638
- effect of chromium620-622
- titanium-aluminum-molyb-
denum alloys600-604
- effect of composition ..600-602

Alloy steel

- embrittlement1557-1598
- at high strength levels
.....1557-1598
- literature survey1558-1561
- mechanical properties .1563-1575
- bainitic structures ...1573-1575
- martensitic structures
.....1563-1573
- transverse mechanical properties
AISI 4320139, 142
- AISI 8627139, 142
- AISI 8630139, 142
- AISI 8740139, 142
- AISI TS 8142139, 142
- AISI TS 8645139, 142
- Ni-Cr-Mo-V steel139, 142

Alloy steel cylinders

- factors affecting quench cracking.
See Quench cracking.

Alloying elements

- effect on grain growth and
recrystallization1388-1392

Alpha iron

- solubility of boron in513-516

Alpha-molybdenum die

- steel1599-1618
- aging characteristics ..1608-1612
- age hardening curves 1608-1612
- aging times producing max-
imum hardness vs. aging
temperatures 1612
- relation between time and
temperature to produce
maximum hardness 1611-1612
- die blocks1612-1615
- hardness1613-1614
- impact strength1614-1615
- effect of tempering
treatments1614-1615
- dimensional stability ..1614-1616
- dilatometer curve 1615
- isothermal transformation
characteristics1600-1609
- diagrams1602-1603
- effect of chemical
composition 1601
- effect of tempering trans-
formation products.1605-1608
- hardness-impact relation 1607
- hardness of transformation
products vs. tempering
temperature 1606
- impact properties of
transformation products
vs. tempering
temperature1606-1607
- microstructure of trans-
formation products ..
.....1603-1605, 1607-1609
- tempering characteristics
.....1606-1608
- practical application 1616

Aluminum

- creep681-699
- correlation creep strain with
temperature-compensated
time683-684

Aluminum (cont.)

- creep
 - effect of prestrain histories
 -681-699
 - prestrained at various
 - temperatures690-691
 - X-ray photograms at
 - various creep strains 683-685
- creep properties687-695
 - effect of prestrain
 - temperature687-691
 - effect of stress recovery 691-695
- dynamic stress-strain
 - relations 39-42
- effect on properties of Cu-
 - Ni-Si alloys332-334
- grain growth
 - time-temperature relation-
 - ship for 1395
- in low carbon steel
 - for control of structure.
 - See Aluminum nitride
 - in steel.
- recrystallization
 - time-temperature relation-
 - ship for 1381
- role in graphitization ..1318-1330
- in SAE 4140-type steels ..828-829
 - effect on dilation during
 - tempering828-829
- solubility in vanadium ... 1145
- stress-rupture data at high
 - temperatures117-119
- stress-strain curves
 -684-686, 689-691, 695-696
- comparison of effects of
 - recovery and stress
 - recovery695-696
- effect of creep straining 684-686
- prestrained at various
 - temperatures689-691
- structure687-695
 - effect of prestrain
 - temperature687-691
 - effect of stress recovery 691-695
- tensile properties691-699
 - effect of prestrain histories
 -681-699
 - effect of stress recovery 691-699
- X-ray photograms
 -688-690, 692-694

Aluminum (cont.)

- X-ray photograms
 - prestrained and stress-
 - recovered to various
 - strains692-694
 - prestrained at various
 - temperatures688-690

Aluminum alloy

- notch tensile properties ..
 -1009, 1017-1018
- variation of necking strain
 - with notch sharpness
 -1017-1018
- variation with notch
 - sharpness 1009

Aluminum, alloy designations

- 2S alloy
 - statistical study of stress-
 - rupture tests 63-85

Aluminum-copper alloys

- deformation strength ..1084-1086
 - effect of temperature 1085-1086
 - effect of volume-free
 - path1084-1086
- elevated temperature tensile
 - properties1075-1088
- effect of dispersions of
 - CuAl₂1075-1088
- heat treatment, for dispersions
 - of CuAl₂1077-1078
- stress-strain curves ...1078-1081
 - effect of CuAl₂ content
 - and size1078-1081
 - effect of testing
 - temperature1078-1081
- X-ray photograms ...1083-1084
 - fractured specimens .1083-1084
 - effect of test
 - temperature1083-1084

Aluminum-magnesium alloys

- grain growth
 - time-temperature relation-
 - ship for 1393

Aluminum-manganese alloys

- grain growth
 - time-temperature relation-
 - ship for1388-1392

Aluminum nitride in steel

- solution and precipitation
 - effect on structure
 - importance of1470-1471

Aluminum nitride in steel (cont.)

- solution and precipitation effect
 - low carbon steels
 - investigated1472-1473
 - mechanism of elongated
 - grain formation ...1491-1495
 - minimum uncombined
 - nitrogen required .1490-1491
- precipitation of aluminum
 - nitride
 - effect of aluminum
 - content1482-1484
 - effect of cold work 1484-1485
 - effect of nitrogen
 - content1483-1484
 - effect of precipitation
 - temperature1478-1479
 - effect of solution
 - temperature1479-1482
 - solution of aluminum
 - nitride1471-1478
 - effect of aluminum
 - content on1473-1474
 - effect of nitrogen
 - content on1474-1475
 - effect of temperature
 - on1471-1473
 - thermal treatment prior to
 - cold work1488-1490

Aluminum-zinc alloys

- effect of copper addition
 - on plastic properties
- copper vs. true stress
 - curves350-351
- stress-strain curves ... 350

Ammonia

- use in nitriding titanium. See under Titanium.

Analysis

- of oxygen and nitrogen in molybdenum. See under Molybdenum.

Anisotropy

- copper655-680
- procedure for investigating657-662

Annealing

- molybdenum
 - effect on recrystallization1452-1454

Annual Address of the President 7**Annual Dinner of ASM ... 27****Annual Meeting of ASM .. 7****Annual Report of the Secretary 16****Annual Report of the Treasurer 11****Atomic numbers**

- correlation with activation energies
 - for creep, rupture and self-diffusion125-127

Austenite

- clustering effects in ...1093-1096
- effect of boron on diffusivity
 - of carbon in 1095
- electron micrographs853, 855
- subgrains in853, 855
- in ferritic stainless steels
 - effect on intergranular corrosion214-218

Austenite decomposition

- 17-25% chromium stainless steel1182-1183
- intermetallic compounds
 - associated with ...1182-1183

Austenite-to-ferrite transformation

- mechanism of1102-1109
- nucleation and growth
 -1103-1109, 1120-1135
- kinetics of the reaction
 -1104-1108
- objections to the concept
 -1103-1109
- orientation relationships 1104
- reversibility of ferrite
 - transformation ..1108-1109
- nucleation and shear ..
 -1108-1109, 1120-1135
- suppression of ferrite
 - formation1109-1112
 - effectiveness factors .. 1110

Austenite grain size

- in case-hardened boron steel456-458

Austenitizing temperature

- effect on quench cracking
 - of hollow steel cylinders 101-102

Beryllium

- solubility in vanadium ... 1140
- stress-rupture data at high temperatures119-121

Boron

- in alloy steel
 - effect on transverse properties ..138-144, 151-153
- in case-carburized steel
 - effect on hardenability 461-465
- effect on Charpy impact
 - traverses1339-1353
 - as a function of distance
 - from the quenched end of end-quenched slabs of steel1339-1353
 - effect of position on transition temperature1352-1353
- effect on hardenability 1089-1135
 - effect of austenitizing temperature 1127
 - mechanism of1089-1135
 - adsorption 1091
 - boron film1090-1091
- effect on quench cracking
 - of hollow steel cylinders 110-111
- effect on temper brittleness of steel. See Boron steel.
- effect on tensile property
 - traverses1339, 1342, 1344-1347, 1349
 - as a function of distance
 - from the quenched end of end-quenched slabs of steel1339, 1342, 1344-1347, 1349
- effects on steel1089-1135
 - adsorption effects ...1091-1093
 - temperature dependence1092-1093, 1123-1124
 - thermodynamic conditions leading to1091-1092
 - grain boundary effect 1090-1093
- in iron-Fe₃B system. See Iron-Fe₃B system.
- in steel
 - effects on diffusivity of carbon in austenite .. 1095
 - strain energy per atom .. 1114

Boron steel

- carbonitrided1365, 1367-1368
- hardenability 1365
- microhardness across case
 - of Jominy bar ..1367-1368
- AISI 80B20 1368
- AISI 94B17 1367
- carburized1367-1370
- hardenability 1367
- microhardness across case
 - of Jominy bar ...1367-1370
- AISI 80B20 1368
- AISI 94B17 1367
- effect of boron on case
 - hardenability461-465
- effect of boron on notch
 - toughness and temper embrittlement
 - hardenability curves ..485, 487
 - influence of boron491-492
 - isothermal embrittlement diagrams486-488
 - nature of temper embrittlement487-491
 - influence of grain size 489-491
 - transition temperatures 485, 487
- hardenability1367-1370
- effect of carbon
 - content1369-1370
 - microhardness across case of Jominy bar1367-1369
- transformation kinetics
 - in1096-1100

Brass

- grain growth
 - time-temperature relationship for 1382
- hardness
 - tempering time - temperature relationship 1378
- notch tensile strength1003-1005, 1016-1018
- effect of notch sharpness1003-1005
- variation of average true stress with notch sharpness at various strain values1016-1017
- variation of necking strain with notch sharpness1017-1018

Brass, alpha

- fatigue, high temperature1023-1035
- effect of grain size.....
 - 1023-1025, 1027-1032, 1035
- on creep rate1030-1032
- on ductility ..1028, 1030-1031
- on fatigue life at various temperatures and stresses ..1023-1025, 1027, 1029-1030, 1032, 1035
- on minimum creep rate 1030
- photomicrographs ...1033-1035
- typical fractures ..1033-1035
- variation in creep rate with dynamic stress 1032
- variation in creep rate with mean stress 1031
- variations in ductility with dynamic stress ...1029, 1031
- variations in ductility with mean stress1028, 1031
- variation in fatigue life with dynamic stress .
 -1026-1027, 1029
- variation in fatigue life with mean stress
 -1023, 1026-1027
- variation in fatigue life with temperature .1027, 1030
- stress-rupture tests, high temperature
 - ..1023, 1026, 1031-1032, 1035
- effect of grain size
 - 1023, 1026, 1031-1032, 1035
- on minimum creep rate at various temperatures and stresses
 -1031-1032, 1035
- on rupture life at various temperatures and stresses1023, 1026

Brittle fracture

- study by torsion test 87-99

Brittleness

- in steel
 - reduction by rheotropic recovery184-196
- in tungsten 405

Carbide phases

- in tempered steel869-871

Carbide precipitation

- in 17-25% chromium stain-less steel 1182

Carbides

- electrolytic isolation of 1588-1589

Carbides, angular appearing

- in high speed tool steels .716-725
- effect of heat treat temperature and time 719-724
- electrolytic extraction of718-719
- electron microscopy of719, 721-724
- nature of723-725
- parameters of724-725
- photomicrographs 720-721, 723

Carbon

- in alloy steel
 - effect on transverse properties135-139
- in case-carburized boron steel
 - effect on hardenability 458-461
- content of ferritic stainless steels
 - effect on intergranular corrosion 207
- effect on quench cracking of hollow steel cylinders107, 109-111
- strain energy per atom .. 1114

Carbonitriding

- AISI 1020 steel
 -1362-1363, 1365-1369
- photomicrographs 1363
- AISI 80B20 steel 1365
- AISI 94B17 steel 1365

Carbon tool steel

- grain size vs. austenitizing temperature for single and double quenching775-776

Carburized steel

- effect of boron on hardenability. See under Hardenability.

Carburizing

- AISI 1020 steel ..1362, 1364-1365
- photomicrographs 1364
- AISI 80B20 steel 1365
- AISI 94B17 steel
 -1365-1366, 1373-1376

Carburizing (cont.)

- AISI 94B17 steel
 hardness vs. carbon
 content1373-1375
 iso-hardness lines ...1374-1376
 photomicrographs 1366
 of titanium259-270

Case hardening

- effect of boron on hardenability.
 See under Hardenability.
 of titanium by nitriding. See
 under Titanium.

Cast iron-nickel-chromium alloys

- corrosion resistance in salt baths.
 See Corrosion resistance.

Charpy impact

- iron-carbon alloys 1305
 iron-carbon-chromium
 alloys 1306
 iron-carbon-chromium-
 manganese alloys 1306
 iron-carbon-chromium-
 nickel alloys 1306
 iron-carbon-chromium-
 nickel-manganese alloys 1308
 iron-carbon-manganese
 alloys 1305
 iron-carbon-nickel alloys 1305
 iron-carbon-nickel-
 manganese alloys 1308
 steel1307-1309
 effect of carbon 1307
 effect of chromium 1309
 effect of manganese ... 1309
 effect of nickel 1308
 titanium-aluminum-chromium
 alloys623-634
 effect of composition ..623-634
 effect of forging practice
627-628
 effect of heat treatment
623-634
 titanium-aluminum-
 molybdenum alloys ..602-607
 effect of composition ..602-607
 effect of cooling rate
 from beta solution
 temperature602-607
 effect of forging practice 606

Charpy impact traverses

- as a function of distance from
 the quenched end of end-
 quenched slabs of steel
1338-1351
 AISI 4320 1338
 AISI 4320 plus boron .. 1339
 AISI 4320 plus rare earths 1340
 AISI 8630 1341
 AISI 8630 plus boron .. 1342
 AISI 8640 1343
 AISI 8640 plus boron and
 rare earths 1344
 corrected to a constant
 tensile strength ...
1338-1339, 1343-1351
 AISI 43201345-1347
 AISI 4320 plus boron
1345-1346
 AISI 4320 plus rare earths
1345-1347
 AISI 86301346-1348
 AISI 8630 plus boron
1346-1347, 1349
 AISI 8640 ...1347-1348, 1350
 AISI 8640 plus boron and
 rare earths 1347-1348, 1351
 in end-quenched 7-inch round
1349-1350, 1352-1353
 effect of position on tran-
 sition temperature .
1349-1350, 1352-1353
 AISI 4320 steel 1352
 AISI 4320 steel plus
 boron 1353
 AISI 4320 steel plus
 rare earths 1353

Chemical segregation

- transverse916-918, 920-921
 various steels 920

Chi phase

- iron-chromium-molybdenum
 alloys799-811

Chlorine, distillation analysis

- of oxygen in gray cast
 iron416-417

Chromium

- in alloy steel
 effect on transverse
 properties144-147

Chromium (cont.)

- content of ferritic stainless steels
- effect on intergranular corrosion 206
- effect on properties of Cu-Ni-Si alloys337-338

Chromium-nickel-molybdenum alloys, 16-25-6

- high temperature properties1051-1052
- stress-rupture tests .1051-1052
- mechanical properties .1042, 1044
- effect of tempering treatments1042, 1044
- substitution of manganese for nickel1039-1055
- Timken alloy 16-25-6
- work softening at elevated temperatures. See Work softening.

Chromium-nickel-molybdenum-manganese alloy

- hardness1042, 1044-1045
- effect of tempering temperature and time 1042, 1044-1045
- high temperature properties1051-1053
- stress-rupture ductility 1052
- compared with 16-25-6 alloy 1052
- stress-rupture tests .1051-1053
- mechanical properties ..1041-1046
- effect of cold work ..1045-1046
- effect of quenching temperature1041-1045
- effect of tempering treatments1042-1045
- microstructure1046-1051
- hot-rolled 1046
- effect of cold work 1048-1050
- effect of water quenching from 1800 to 2150 °F1046-1048, 1050

Chromium-nickel steel, austenitic

- electrical resistivity959-961
- effect of aging960-961
- effect of phosphorus content959-961
- grain size961-964
- effect of solution temperature961-964

Cr-Ni steel, austenitic (cont.)

- hardness952-958
- effect of aging temperature953, 956-958
- effect of aging time952-954, 957
- effect of carbon content 952
- effect of cooling rate from solution temperature 958
- effect of phosphorus content954-958
- effect of solution temperature953, 955-956
- lattice parameters958-959
- austenite 959
- carbide958-959
- microstructure960-968
- effect of aging time ..963-966
- effect of phosphorus content 965
- effect of quenching strains966-968
- etchants 961
- grain size961-964
- photomicrographs962, 964, 966, 968
- residual carbide content after solution treatment ..961-964
- precipitation hardening ..948-971
- effect of aging temperature953, 956-958
- effect of aging time952-954, 957
- effect of carbon content 952
- effect of cooling rate from solution temperature 958
- effect of phosphorus content954-958
- effect of solution temperature953, 955-956
- residual carbide content after solution treatment ..961-964
- effect of solution temperature961-964

Chromium-silicon steels

- hardenability1505-1515

Coarsened grains

- high speed steel779, 781
- effect of multiple annealing779, 781
- means of eliminating ..779, 781

Cold work

- effect on grain growth ...
.....1385-1386, 1389-1390
- effect on recrystallization
.....1381, 1385
- of low carbon steel
 - effect on precipitation of
aluminum nitride ..1484-1485
- of molybdenum
 - effect on recrystallization
.....1452-1453

Constitution diagrams

See Phase diagrams.

Constitutional supercooling

-1217-1218

Cooling rates

- correlation between ideal
diameter and distance on
end-quench bar907-910
- correlation curves of equal
cooling times907-908
- in end-quench bars and
rounds907-908
- correlation with hardness 915
- in end-quenched 7-inch
rounds1339-1341, 1352
- as a function of the distance
from the quenched
end1341, 1352
- comparison with Jominy
specimen1341, 1352
- half-temperature time ...
.....890, 892, 900-902
- for end-quenched bars 900-902
compared with theoretical
curve900-902
- for various size rounds
and steels890, 892
- in rounds and end-quench
bars889-890
- specimen for determining 884-885
- 1350 °F to terminal temper-
ature times890, 894-896
- for end-quench bars ...
.....890, 902-904
- for steel rounds890, 894
- variation of H value .898-899, 902
- with size and position .899, 902
- in round and end-quench
bars899, 902
- with temperature .898-899, 902

Cooling rates (cont.)

- in various quenching media
.....1235-1236
- time-temperature curves 1235

Copper

- additions to Al-Zn alloys
 - effect on plastic properties
.....348-353
- ductility661-664
- effect of torsional pre-
strain661-664
- hardness665-666
- effect of torsional strain
.....665-666
- ingot cast centrifugally ..659-660
- macrostructure 660
- mechanical anisotropy ...655-680
- procedure for investigating
.....657-662
- notch tensile properties ..
...1006-1008, 1011, 1017-1018
- variation of necking strain
with notch sharpness
.....1017-1018
- variation with notch sharp-
ness1006-1008, 1011
- notch tensile strength .1003-1005
- effect of notch sharpness
.....1003-1005
- solubility in vanadium ... 1155
- tensile fracture stress ...661-666
- effect of torsional pre-
strain661-666

Copper-aluminum alloys

- flow stress1080-1082
- effect of test temperature
.....1080-1082

Copper-nickel-silicon-aluminum alloys

- development of precipitation-
hardenable alloy
- evaluation of Cu-Ni-Si
base alloys338-344
- comparison with copper-
beryllium alloy ...342-344
- effect of solution treat-
ment temperature on
hardness 341
- tensile properties ... 339

Cu-Ni-Si-Al alloys (cont.)

- development of precipitation-
hardenable alloy
- investigation of Cu-Ni-Si
alloys
 - effect of aluminum
additions332-334
 - effect of chromium
additions337-338
 - effect of iron
additions332-333
 - effect of magnesium
additions337-338
 - effect of manganese
additions333-335
 - effect of tin additions 336-337
 - effect of titanium
additions335-336
- investigation of Cu-Ni-Si
system330-332
- effect of nickel and silicon
on hardnesses 331

Corrosion

- stainless steel, Types 430 and
4421204-1205
- effect of welding and post-
weld annealing1204-1205

Corrosion resistance

- of cast Fe-Ni-Cr alloys in
neutral salt baths
- advantages of salt bath
heating157-158
- alloys investigated160-161
- effect of alloy grain size 179-181
- effect of alternate
immersion 173
- effect of bath chemistry
and rectifiers160-170
- effect of cyanide pre-
treatment181-182
- effect of Ni and Cr
content 163-164, 172, 181-182
- effect of partial immersion
.....173-175
- effect of salt bath
composition175-179
- effect of sludge in bath 171-173
- effect of sodium fluoride
in bath170-171
- salt baths investigated .170-175

Creep

- aluminum681-699
 - correlation creep strain
with temperature-
compensated time ...683-684
 - effect of prestrain
histories681-699
 - prestrained at various
temperatures690-691
 - X-ray photograms at various
creep strains683-685
- annealed metals .683-687, 696-698
- equilibrium subgrain
structures696-698
- correlation between subgrain
structures and properties
.....681-699
- correlation with rupture and
self-diffusion activation
energies
as function of atomic
numbers125-127
- equation for total creep ..113-115
- mechanisms681-682

Creep curves

- nickel alloys703-714
 - effect of solid solution alloy
content on parameter "A"
.....708-709, 713
 - reproducibility703-705
 - variation of ϵ_0 with solid
solution alloy content
.....708-709, 714
 - variation of slope with solid
solution alloy content
.....708-709, 712
- nickel-cobalt alloys .705-707, 710
- nickel-iron alloys ...705-707, 710
- nickel-titanium alloys ...
.....705, 708, 711
- nickel-tungsten alloys ...705, 709

Creep parameters

- nickel701-714
 - effect of solid solution
alloying elements ...701-714
- nickel-cobalt alloys706-707
- nickel-iron alloys706-707
- nickel-titanium alloys ...706-707
- nickel-tungsten alloys ...706-707

Creep properties

- aluminum687-695
- effect of prestrain temperature687-691
- effect of stress recovery 691-695

Creep rates

- nickel-cobalt alloys706-708
- nickel-iron alloys706-708
- nickel-titanium alloys ...706-708
- nickel-tungsten alloys ...706-708

Critical temperatures

- AISI 1020 steel1278-1279
- for various burning times
- of a rocket1278-1279
- effect of high heating
- rates1274-1278
- AISI 1020 steel1274-1275
- AISI 1042 steel1274-1275
- AISI 1080 steel1274-1276
- AISI 4130 steel1276-1278
- effect of heat treatment
-1277-1278
- steel1270-1284
- effect of tensile stress 1279-1281
- elevation by high heating
- rates1270-1284
- apparatus for determining1271-1274
- method of determining
-1272-1274

Cubic lattice, face-centered

- interstitial holes in1094-1096

Cylinders

- of hollow alloy steel
- factors affecting quench cracking. See Quench cracking.

Deformation strength

- aluminum-copper alloys 1084-1086
- effect of temperature 1085-1086
- effect of volume-free
- path1084-1086

Dendritic freezing

- in alloys1214-1222
- solid-liquid interface 1215-1217

Die steel

- See also alpha-molybdenum die steel.

Die steel (cont.)

- alpha-molybdenum
- hardenability1601-1603
- based on transformation
- diagrams1601-1603
- low tungsten775, 777
- grain size vs. austenitizing
- temperature for single and
- double quenching ...775, 777

Diffusion

- activation energy 826
- carbon in austenite 826
- effect of silicon 826
- carbon in ferrite 826
- effect of silicon 826

Diffusion coefficients

- hydrogen in zirconium .. 644

Diffusion rates

- hydrogen in zirconium .. 644

Dilatation study

- of gamma loop
- in iron-vanadium system
-278-283
- in iron-vanadium-titanium
- system283-288

Dilatometric cooling curves

- steel TS 81171121-1123
- effect of boron content
-1121-1123

Ductility

- copper661-664
- effect of torsional pre-strain661-664
- effect of notch sharpness on
-1003-1005
- annealed brass1003-1005
- hard drawn copper ..1003-1005
- ratio of unnotched ductility and
- notch ductility vs. unnotch
- necking strain1014-1016

Dynamic loading of metals

- definition of 35
- delay of plastic strain ... 47-48
- effect of stress on 48
- effect of temperature on 48-49
- maximum limiting stress 49-50
- relationship to brittle
- transition 51-52
- types of alloys showing
- delay 50-51

Dynamic loading of metals (cont.)

- dynamic stress-strain relations
 - 38-42
 - for aluminum 39-42
- impact and strain propagation
 - 35-38
 - experimental vs. theoretical
 - strain distribution ... 37-38
 - impact velocity-maximum
 - strain equation 36
 - velocity of propagation
 - equation 36
- mechanism of delay time
 - dislocations and yielding 55-59
 - Frank-Read dislocation
 - source 57-58
 - mechanism of plastic
 - deformation 55
- preyield microstrain 52
- microstrain vs. time ... 53
- strain rate effects 44
 - on proportional limit and
 - ultimate strength ... 46-47
 - strain rate vs. time 45
- tension-impact properties
 - critical impact velocity . 43-44
 - static vs. dynamic tensile
 - properties 42-43
 - time to initiate yielding
 - effect of aging time and
 - temperature on 53-55

Effectiveness factors

- austenite-to-ferrite trans-
 - formation 1110

Election of Officers 26**Electrical resistivity**

- austenitic chromium-nickel
 - steel 959-961
 - effect of aging 960-961
 - effect of phosphorus
 - content 959-961

Electrical resistivity measurements

- of nitrated titanium 559-560

Electron micrographs

- high speed steel 743-744
- iron-carbon alloys
 - 857-864, 872-873
 - effect of tempering
 - temperature 857-864

Electron micrographs (cont.)

- iron-carbon alloys
 - effect of tempering temperature
 - 0.15% carbon alloy ..
 - 861, 863-864
 - 0.4% carbon alloy ... 861-864
 - 0.8% carbon alloy ...
 - 859-861, 863-864
 - 1.4% carbon alloy ...
 - .. 857-859, 863-864, 872-873
 - retained austenite 853, 855
 - subgrains in iron-carbon
 - alloy 853, 855
 - tempered martensite
 - 853-855, 878-879
 - comparison of rotary and
 - static shadowing
 - 853-854, 878-879
 - subgrains in iron-carbon
 - alloys 853, 855
 - tempered medium carbon
 - steel 824-825
 - effect of silicon 824-825

Electron microscope study

- of Ti-7.54% Cr alloy 243-248

Electron microscopy

- rotary shadowing 853-854, 878-879
- comparison with static
 - shadowing .. 853-854, 878-879

Elevated temperature properties

- of titanium alloys 584-585

Elevated temperature tensile properties

- aluminum-copper alloys 1075-1088
- effect of dispersions of
 - CuAl₂ 1075-1088

Embrittlement

- alloy steel 1557-1598
 - at high strength levels. 1557-1598
 - literature survey 1558-1561
- relation to nature and sequence
 - of carbide structures
 - 1581-1584
 - SAE 2340 steel 1581
 - SAE 4330 steel 1582
 - SAE 4340 steel 1581, 1583
- time-temperature relations
 - 1581-1583
 - SAE 2340 steel 1581
 - SAE 4330 steel 1582
 - SAE 4340 steel 1581

Equilibrium structures

iron-chromium-molybdenum
alloys799-811

Fatigue

specimens1255-1256

Fatigue cracks

in torsion specimens ...1257-1261
in transverse bend specimens
..... 1257-1260

Fatigue limit

SAE 4340 steel
effect of inclusions ..1254-1260
free of inclusions
..... 1257, 1260-1263

Fatigue, high temperature

brass, alpha1023-1035
effect of grain size.....
1023-1025, 1027-1032, 1035
on creep rate1030-1032
on ductility ..1028, 1030-1031
on fatigue life at various
temperatures and
stresses1023-1025,
1027, 1029-1030, 1032, 1035
on minimum creep rate..1030
photomicrographs ...1033-1035
typical fractures ..1033-1035
variation in creep rate with
dynamic stress 1032
variation in creep rate with
mean stress 1031
variations in ductility with
dynamic stress ...1029, 1031
variations in ductility with
mean stress1028, 1031
variations in fatigue life with
dynamic stress 1026-1027, 1029
variations in fatigue life with
mean stress ..1023, 1026-1027
variation in fatigue life with
temperature1027, 1030
specimen1022-1023

Fatigue strength

SAE 4340 steels1254-1269
effect of inclusion....1254-1269

Ferrite

single crystals
flow and fracture of.
See Single crystals.

Ferrite, proeutectoid

kinetics of isothermal
formation1105-1107
number of ferrite particles per
unit area as a function of time
at 1375 °F for SAE 8620 and
86B20 steels1124-1125
radius of largest ferrite particle
present as a function of time
at 1350 °F for SAE 8620 and
86B20 steels1124-1125

Ferritic stainless steels

See Stainless steels, ferritic.
intergranular corrosion of.
See under Stainless steels.

Fish-scale fractures. 728-730, 762-763
high speed steel762-763

Flow stress

copper-aluminum alloys.1080-1082
effect of test temperature
.....1080-1082

Fracture

types encountered in torsion
test 92-97

Fracture characteristics

of annealed tungsten
at various temperatures.399-405

Gamma iron

solubility of boron in....508-510

Gamma loop study

of iron-vanadium system .278-283
of iron-vanadium-titanium
system283-288

Gilding metal

hardness
tempering time -
temperature relationship.1380

Glide planes

in ferrite single crystals.
See under Single crystals.

Grain coarsening

high speed steel
765-770, 773-774, 776, 778-779
after second austenitizing
treatment765-770
effect of prequench
temperature765-770

Grain coarsening (cont.)

- high speed steel
 - continuous and discontinuous769-770
 - effect on quenched hardness 774
 - effect of slow heating on 776, 778-779
 - effect on tempered hardness773-774

Grain growth

- high speed steel727-773
 - coarsening temperature during second austenitizing treatment as a function of first austenitizing temperature 735, 739
 - on double hardening ...761-773
 - effect of annealing variables 743-745
 - history728-730
 - nature of process 733-735, 746-758
 - role of proeutectoid carbides 735-739
 - on single hardening...759-761
- of molybdenum1454-1455
- time-temperature relationship for comparison with recrystallization1381, 1388, 1395-1396
- effect of cold work 1385-1386, 1389-1390
- effect of second phase .1388-1391
- effect of solid solution.. 1391-1392, 1394
- effect of specimen size1383, 1385, 1389
- equation for 1382
- importance of grain size control 1377
- master grain growth curves 1387
- theoretical considerations1392-1396
- with aluminum 1395
- with aluminum-magnesium alloys 1393
- with aluminum-manganese alloys1388-1392
- with brass 1382
- with iron1386, 1395
- with nickel1384, 1395
- with zirconium1387, 1395

Grain growth behavior

- high speed steel739-743
 - significance of starting structure739-743

Grain growth, discontinuous

- high speed steel759-798
 - means of avoiding on second hardening776-779

Grain size

- austenitic chromium-nickel steel961-964
 - effect of solution temperature961-964
- brass, alpha1021-1035
 - effect on high temperature fatigue1021-1035
- carbon tool steel775-776
 - vs. austenitizing temperature775-776
- effect on temper brittleness 489-491
- effect of tempering time and temperature. See under Grain growth or Recrystallization.
- high speed steel....733-735, 739
 - effect of austenitizing temperature733-734
 - effect of second austenitizing temperature as a function of prequenching temperature734-735, 739
- low tungsten die steel....775-776
 - vs. austenitizing temperature775-776
- of molybdenum
 - effect on ductility ...1463-1464
- steel1237-1240, 1243
 - determination 1237
 - effect of austenitizing temperature .1237-1240, 1243
 - photomicrographs ...1237-1238

Grain structure

- of low carbon steel
 - control with aluminum nitride. See Aluminum nitride in steel.

Graphitization

- effect of prior heat treatment 1321-1323
- influence of per cent aluminum and nitrogen in solution 1321-1324

Graphitization (cont.)

- role of aluminum in....1318-1330
- role of nitrogen in1318-1330

Gray cast iron

- oxygen content of cupola-melted iron
- chlorine distillation analysis 416-417
- equilibrium relations ..412-414
- metallographic examination 415-416
- vacuum-fusion analysis.414-415

Half-temperature time

- correlation with hardness 915
- for end-quenched bars ...900-902
- compared with theoretical curve900-902
- for various size rounds and steels890, 892

Hardenability

- of alloy steels
 - effect of composition on 131, 135
- alpha-molybdenum die steels 1601-1603
- based on transformation diagrams1601-1603
- boron steels...485-487, 1369-1370
- carbonitrided 1365
- carburized 1365
- carbonitrided steel
 - 1362, 1365, 1367-1369
 - AISI 1020 .1362, 1365, 1367-1369
 - AISI 80B20 1365
 - AISI 94B17 1365
- carburized steel ..1362, 1365-1369
- AISI 10201362, 1365-1369
- AISI 80B20 1365
- AISI 94B171365-1366
- photomicrographs .. 1366
- of a case-carburized boron steel
 - austenite grain size ...456-458
 - composition of steel ... 447
 - correlation of microstructure and hardness.453-454, 466-468
 - effect of boron on hardenability461-465
 - boron vs. austenite transformation462-463
 - effect of carbon on hardenability458-461

Hardenability (cont.)

- of a case-carburized boron steel
 - estimation of case hardenability468-473
 - estimation of ideal diameters454-456
 - hardenability results ...448-453
 - importance of boron steels 446
- of commercial steels
 - quenched in salt and water. See Hardenability test.
- comparison of curves obtained on Jominy specimens and end-quenched 7-inch rounds1336-1337
- correlation curves917-921
- based on equal 50, 80 and 95% martensite positions 917-921
- effect of austenitizing temperature 1127
- effect of boron1089-1135
- mechanism of1089-1135
- adsorption 1091
- boron film1090-1091
- effect of carbon..1337, 1341-1342
- effect of lancerramp (rare earth)1337, 1342
- effect of section size..... 1343
- effect of strain on919-921
- equal hardness relationships911, 913-914
- between distance on end-quench bar and center and midway position of rounds911, 913-914
- mechanisms of alloying elements1100-1102
- ferrite reaction, proeutectoid1101-1102
- effect of molybdenum 1102
- pearlite reaction 1101
- effect of molybdenum 1101
- reproducibility of end-quench test928-947
- titanium-aluminum-chromium alloys611-613
- effect of composition ..611-613
- titanium-aluminum-molybdenum alloys592-595
- effect of composition on 594-595
- procedure592-593

Hardenability test

- Jominy-type in molten salt experimental procedure 1501-1505
- hardenability with salt vs. water 1505-1509
- importance of marquenching 1500-1501
- mechanism of salt quenching 1509-1516
- microstructures 1507-1510
- relationship to water quench 1518
- salt stability studies.. 1516-1518
- steels tested 1501
- structure with salt vs. water 1506
- time-temperature curves, salt vs. water for Cr-Si steel 1512-1515
- for SAE 3140 steel. 1513, 1515
- for 18-8 stainless steel 1509-1511

Hardness

- alpha-molybdenum steel die blocks 1613-1614
- as a function of tempering temperature 1563-1566
- SAE 1340 steel 1563, 1565
- SAE 2340 steel 1563-1564
- SAE 4330 steel 1563, 1567
- SAE 4340 steel 1563, 1566
- austenitic chromium-nickel steel 952-958
- effect of aging temperature 953, 956-958
- effect of aging time. 952-954, 957
- effect of carbon content 952
- effect of cooling rate from solution temperature 958
- effect of phosphorus content 954-958
- effect of solution temperature 953, 955-956
- chromium-nickel-molybdenum-manganese alloy 1042, 1044-1045
- effect of tempering temperature and time. 1042, 1044-1045
- copper 665-666
- effect of torsional strain. 665-666
- correlation with cooling rates 915

Hardness (cont.)

- correlation with half-temperature time 915
- correlation with 1350-T time 915
- differences between end-quench and round bars 909-921
- at equal half-temperature times 909-910, 912-914
- effect of differences in strain during cooling 919-921
- for 95, 80 and 50% martensite positions 897-898
- for end-quenched bars. 898
- for various size rounds and steel grades 897
- for various 1350-T times.. 912-915
- differences between end-quench and round bars 912-915
- iron-carbon alloys 856-857
- vs. tempering temperatures 856-857
- effect of carbon content 856-857
- tempering time and temperature relationship
- for brass 1378
- for gilding metal..... 1380
- for nickel silver 1380
- vs. grain size 1381
- for zirconium 1379
- titanium-aluminum-chromium alloys 611-615, 619-620, 623-625, 630-639
- titanium-aluminum-molybdenum alloys..... 600, 602, 605-606
- titanium-chromium alloy 1069
- titanium-iron alloys 1069
- titanium-molybdenum alloy 1069
- Types 309 and 310 stainless steel 1288, 1292
- effect of aging treatments 1288, 1292
- vanadium 1139
- vs. time for isothermally transformed specimens.. 1061-1062, 1065-1066, 1068, 1073
- RC-130A alloy 1073
- Ti-2.91% Mn alloy.... 1061-1062, 1065
- Ti-7.72% Mn alloy.... 1062, 1066, 1073
- Ti-12.3% Mn alloy .1062, 1068

Hardness traverse

- 4140 steel 2¼-inch round with center and two midway inserts917, 921
- 4340 steel 3-inch round with center pin insert.915-916, 920
- effect of strain on hardness 920
- photomicrographs 916

Heat treatment

- aluminum-copper alloys .1077-1078
- for dispersion of CuAl₂ 1077-1078
- of ferritic stainless steels
- effect on intergranular corrosion209-214
- of titanium alloys.
- See Titanium alloys.
- titanium-aluminum-chromium alloys622-634
- effect on mechanical properties622-634
- titanium-aluminum-molybdenum alloys 593
- of titanium-molybdenum alloys
- correlation with microstructure and mechanical properties292-311

Helical fracturing..664-668, 671-672**High speed steel**

- coarsened grains779, 781
- effect of multiple annealing 779, 781
- means of eliminating..779, 781
- coarsening temperature as a function of first austenitizing temperature 770-773, 786-787
- coarsening temperature during the second austenitizing treatment as a function of the first austenitizing temperature 792-793
- electron micrographs743-744
- fish-scale fractures762-763
- grain coarsening 765-770, 773-774, 776, 778-779
- after second austenitizing treatment765-770
- effect of prequench temperature765-770
- continuous and discontinuous769-770

High speed steel (cont.)

- grain coarsening
- effect on quenched hardness 774
- effect of slow heating on776, 778-779
- effect on tempered hardness773-774
- grain growth727-773
- coarsening temperature during second austenitizing treatment as a function of first austenitizing temperature 735, 739
- on double hardening...761-773
- effect of annealing variables743-745
- history728-730
- nature of process..... 733-735, 746-758
- role of proeutectoid carbides735-739
- on single hardening....759-761
- grain growth behavior
- significance of starting structure739-743
- grain growth, discontinuous 759-798
- means of avoiding on second hardening776-779
- grain size.....733-735, 739
- effect of austenitizing temperature733-734
- effect of second austenitizing temperature as a function of prequenching temperature734-735, 739
- grain size vs. austenitizing temperature
- after a single hardening treatment759-761
- grain size vs. second austenitizing temperature761-762
- microstructure 736-738, 762, 764-766, 779-785, 790-792, 795-798
- austenite subgrain in martensite 795
- mixed grain 762, 764-765, 779-785
- quenched from various temperatures736-738
- subgrain structure 782-784, 796-798

High speed tool steel

See Tool steel.

High temperature fatigue

See Fatigue, high temperature.

High temperature propertieschromium-nickel-molybdenum
alloy

stress-rupture tests..1051-1052

chromium-nickel-molybdenum-

manganese alloy ..1051-1053

stress-rupture ductility 1052

compared with 16-25-6

alloy 1052

stress-rupture tests..1051-1053

High temperature stress-rupture testsSee Stress-rupture tests,
high temperature.**High temperature transformations**

17-25% chromium stainless

steel1176-1213

delta ferrite to aggregate

of austenite and car-

bides1197-1201

mechanism involved 1200-1201

involving delta ferrite.1193-1197

growth of austenite into

delta ferrite1193-1196

substructures1195-1196

veining1195-1196

in ferritic stainless steels

..... 1176-1213

Hydride phase

in zirconium.640-642, 644, 646-654

diffraction pattern652-653

identification649-654

Hydrogen

in zirconium640-654

diffusion rates 644

effect on ductility640-642

equilibrium pressure ..644-646

solubility642-644

Impactenergy absorbed as a function
of decomposition temper-

ature841, 843

AISI 1340 steel841, 843

AISI 2340 steel841, 843

AISI 5140 steel841, 843

Impact (cont.)

energy vs. temperature...837-843

effect of decomposition

products837-843

AISI 1340 steel

..... 837-838, 842-843

AISI 2340 steel.....837-843

AISI 5140 steel

.....837, 840, 842-843

Impact characteristics

SAE 4340 steel1592-1593

effect of forming decreasing

amounts of martensite

prior to formation of

bainite1592-1593

effect of quenching 1593

Impact energy

as a function of tempering

temperature1563-1566

SAE 1340 steel.....1563, 1565

SAE 2340 steel1563-1564

SAE 4330 steel.....1563, 1567

SAE 4340 steel.....1563, 1566

as a function of tempering time

..... 1563-1566, 1568-1570

effect of tempering temper-

ature ...1565-1566, 1568-1570

SAE 13401565-1566, 1568

SAE 23401565, 1568

SAE 4330 1569

SAE 43401564-1565, 1569

effect of tempering time and

temperature1567-1576

SAE 1340 steel

.....1567, 1571-1573, 1575

SAE 2340 steel

...1567, 1570, 1572-1574, 1576

SAE 4330 steel

.....1567, 1569-1573, 1575

SAE 4340 steel.1567, 1569-1574

SAE 3312 steel

..... 1299-1300, 1302-1304

at various testing tempera-

tures ...1299-1300, 1302-1304

effect of cooling rate...

..... 1299-1300, 1302-1304

transition curves

1570-1571, 1574-1575, 1582-1585

bainitic structures

..... 1574-1576, 1582-1585

tempered martensite ..

..... 1570-1571, 1582-1585

Impact loading

See Dynamic loading of metals.

Impact properties

Charpy V notch for nodular iron422-443
 effect of notch sharpness on1595-1597
 Super HY-Tuf and SAE 4340 steels 1591
 of titanium-molybdenum alloys297-303
 transverse of alloy steels effect of composition on. See Transverse mechanical properties.

Indium arsenic - antimony system

microstructures391-395
 phase diagram 391
 thermal analysis390-391
 X-ray analysis392-396

Induction heat treatment

to surface harden titanium 270-273

Intergranular corrosion

of ferritic stainless steels.
 See under Stainless steels.

Interstitial holes

in face-centered cubic lattice1094-1096

Interstitial solid solutions

effective diameter of solute atoms1168-1175
 equations1169-1171
 strain energy1112-1116
 as a function of the distance from the solute atom 1114-1116
 diameter of interstitial atoms 1112
 boron 1113
 carbon 1113
 equations 1112
 nitrogen 1113
 equations 1114
 peaks1115-1116
 per atom 1114

Iron

effect on properties of Cu-Ni-Si alloys332-333

Iron (cont.)

grain growth
 time-temperature relationship for1386, 1395
 nodular, notch ductility.
 See Nodular iron.

Iron-carbon alloys

Charpy impact 1305
 electron micrographs
 857-864, 872-873
 effect of tempering temperature857-864
 0.15% carbon alloy ..
 861, 863-864
 0.4% carbon alloy....861-864
 0.8% carbon alloy ...
 859-861, 863-864
 1.4% carbon alloy ...
 ..857-859, 863-864, 872-873
 graphitization1321-1326
 effect of aluminum ..1323-1326
 influence of nitrogen.1321-1326
 hardness vs. tempering temperatures856-857
 effect of carbon content.856-857
 low temperature properties977-985
 strain hardening985-991
 effect of carbon content 990
 effect of ferrite grain size990-991
 effect of temperature 989-991
 tensile data979, 983
 total strain977-985
 effect of carbon content979-985
 effect of ferrite grain size977-985
 effect of heat treatment980-985
 effect of temperature977, 985
 yield point991-995
 effect of ferrite grain size991-994
 effect of heat treatment991-992
 effect of temperature 994-995
 effect of twinning ... 994

Iron-carbon alloys (cont.)

- microstructures
 - ..978-979, 980, 982, 1323-1327
 - carbide stringers979, 982
 - grain size978, 980
- strain hardening exponent..987-991
 - effect of carbon content 990
 - effect of ferrite grain size990-991
 - effect of temperature ..989-991
- stress-strain curves985-987
 - effect of testing temperature985-987
- subboundary carbide865-867
 - thickness of865-867
 - equation for determining 866
- subboundary carbide precipitation867-875
 - first stage of tempering..867-869
 - third stage of tempering..869-875
 - nature of carbide869-871
 - nature of reaction....871-874
 - relationship to embrittlement874-875
- subgrains in tempered martensite864-865
 - size of864-865
 - equation for determining 865
- temper embrittlement ... 1305
- tempering851-881
 - microstructural changes on851-881
 - transition temperatures.. 1305

Iron-carbon-chromium alloys

- Charpy impact 1306
- temper embrittlement ... 1306
- transition temperatures .. 1306

Iron-carbon-chromium-manganese alloys

- Charpy impact 1306
- temper embrittlement ... 1306
- transition temperatures .. 1306

Iron-carbon-chromium-nickel alloys

- Charpy impact 1306
- temper embrittlement ... 1306
- transition temperatures .. 1306

Iron-carbon-chromium-nickel-manganese alloys

- Charpy impact 1308
- temper embrittlement ... 1308
- transition temperatures .. 1308

Iron-carbon-manganese alloys

- Charpy impact 1305
- temper embrittlement ... 1305
- transition temperatures .. 1305

Iron-carbon-nickel alloys

- Charpy impact 1305
- temper embrittlement ... 1305
- transition temperatures .. 1305

Iron-carbon-nickel-manganese alloys

- Charpy impact 1308
- temper embrittlement ... 1308
- transition temperatures .. 1308

Iron-chromium-molybdenum alloys

- equilibrium structures ...799-811
- heat treatment800-801
- lattice constant801-802
 - Chi phase801-802
 - "N" phase 802
- metallography802, 804
- phase diagrams803, 805
- photomicrograph802, 804
- X-ray diffraction801-802
 - Chi phase801-802
 - "N" phase 802

Iron-Fe₂B system

- influence of small amounts of boron
 - Fe-Fe₂B diagram516-517
- iron-boron phase diagrams 501-503
- microstructures505-507
- previous work on iron-boron system500-503
- procedure503-508
- reaction isotherms 508
- solubility of boron in alpha iron513-516
 - microstructures 515
- solubility of boron in gamma iron508-510
 - microstructures511-512
- thermal analysis508-510
- types of solid solutions formed517-519

Iron-nickel-chromium alloys

- corrosion resistance of castings in neutral salt baths. See Corrosion resistance.

Iron-vanadium system

- gamma loop study278-283

Iron-vanadium-titanium system

gamma loop study283-288

Isothermal austenite transformation

in 17-25% chromium stainless

steel ...1180-1189, 1191-1193

data1180-1182

reaction rate curves..1191-1193

transformation products

..... 1183-1189

effect of transformation

temperature1183-1189

TTT curves1180-1181

Isothermal embrittlement diagrams

for boron steel486-488

Isothermal formation

martensite1105, 1107-1108

kinetics of1105, 1107-1108

Isothermal transformation

of titanium-chromium alloys.

See under Titanium-chromium alloys.

Isothermal transformation diagrams

Ti-2.91% Mn alloy....1059-1060

Ti-7.72% Mn alloy

..... 1061-1062, 1072

Ti-12.3% Mn alloy ...1061, 1065

Isotopes

oxygen-18

use in determining oxygen

in titanium and zirconium

..... 528

Izod impact

Types 309 and 310 stainless

steel1288, 1292

effect of aging treat-

ments1288, 1292

relation to microstructure 1292

Jominy end-quench test

cooling curves...935-939, 941-944

variation in....936-939, 941-944

effect of delay during

specimen transfer .938-939

effect of specimen

positioning 935

effect of surface scale.944-945

effect of water spray

height943-944

Jominy end-quench test (cont.)

cooling curves

variation in

effect of water tem-

perature941-942

for several end-quench

positions936-937

cooling rates

890, 894-896, 902-904, 907-910

correlation between ideal di-

ameter and distance on

end-quench bar907-910

correlation curves of equal

cooling times in end-quench

bars and rounds907-908

correlation with hardness 915

1350 °F to terminal tem-

perature times

.....890, 894-896, 902-904

hardness909-921

difference between end-quench

and round bars....909-921

at equal half-temperature

times909-910, 912-914

effect of differences in strain

during cooling919-921

for various 1350-T times

..... 912-915

hardness gradient940-944

effect of variation in speci-

men transfer time ..940-942

effect of water spray height

..... 943-944

effect of water temperature 942

quenching constant886-907

calculation of H value.. 886

variation of H value...887-907

at half-temperature time

..... 905-907

importance of severity of

quench

891, 896, 898-899, 901-907

with specimen size ..887-904

with temperature ...887-904

quenching fixture934-935

couple assembly and speci-

men in position 935

reduction in surface temperature

during transfer of specimen

from furnace to quenching

fixture937-938

specimen884-885

Jominy end-quench test (cont.)

- temperature measurements during quench929-933
- magnitude of error930-933
- thermal reproducibility ..928-947
- test specimen930-932
- thermocouple assembly
..... 930-932, 935
- time-temperature relation
..... 938-939, 941-944
- effect of delay during specimen transfer938-939
- effect of surface scale..944-945
- effect of water spray
height942-943
- effect of water temperature941-942

Jominy-type test

- using molten salt bath.
- See Hardenability test.

Lattice constants

- iron-chromium-molybdenum
alloys801-802
- Chi phase801-802
- "N" phase 802
- nickel702-703
- effect of alloying elements
.....702-703

Lattice parameters

- austenitic chromium-nickel
steel958-959
- austenite 959
- carbide958-959

Low carbon steel

- aluminum nitride effect on
structure. See Aluminum
nitride in steel.

Low temperature properties

- iron-carbon alloys979-991
- strain hardening985-991
- effect of carbon content 990
- effect of ferrite grain
size990-991
- effect of temperature 989-991
- tensile data979, 983
- total strain977-985
- effect of carbon content
.....979-985

Low temperature properties (cont.)

- iron-carbon alloys
- total strain
- effect of ferrite grain
size977-985
- effect of heat treatment
.....980-985
- effect of temperature 977, 985
- yield point991-995
- effect of ferrite grain
size991-994
- effect of heat treatment
.....991-992
- effect of temperature 994-995
- effect of twinning ... 994

Low temperature testing

- tensile properties975-977
- apparatus975-977
- recording diameter
gage976-977
- schematic diagram .. 976

Magnesium

- effect on properties of Cu-
Ni-Si alloys337-338

Magnetization

- medium carbon steels ...813-817
- vs. temperature813-817
- effect of silicon813-816
- with different retained
austenite contents ... 815

Manganese

- effect on properties of Cu-
Ni-Si alloys333-335

Manganese-chromium-molybdenum steels

- hardenability1505-1509

Marquenching

- in molten salt. See Harden-
ability test.

Martensite

- hardness for 95, 80 and 50%
martensite positions
.....897-898
- for end-quenched bars . 898
- for various size rounds
and steel grades 897
- kinetics of isothermal
formation1105, 1107-1108

Martensite (cont.)

- relationship between end-quench bars and center, $\frac{1}{2}$ radius and $\frac{3}{4}$ radius positions917-921

Martensite formation

- nature of 1246
- nucleation and growth theory1246-1248
- nucleation and shear theory1246-1248
- rate of1243-1247
- as a function of transformation temperature 1243-1245
- effect of austenitizing temperature1243-1247
- effect of grain size ..1243-1246

Martensite reaction

- 17-25% chromium stainless steel 1183

Martensite, tempered

- electron micrographs853-855
- comparison of rotary and static shadowing853-854
- subgrains in iron-carbon alloys853, 855
- subgrains in iron-carbon alloys864-865
- size of864-865
- equation for determining 865

Martensite transformation

- as a function of transformation temperature1243, 1245
- effect of austenitizing temperature on M_s
-1239-1240, 1243
- effect of cooling rate on M_s 1240, 1242-1243
- effect of grain size on M_s
-1240-1243
- influence of heat treating variables1225-1253
- literature survey1226-1227
- quench-temper method for determining1228-1236
- austenitizing temperature
-1239-1240
- cooling rate1240, 1242
- grain size1240-1242

Martensite transformation (cont.)

- influence of heat treat variables
- thermal analysis method for determining ...
-1236-1237, 1242-1244
- austenitizing temperature
- 1243
- cooling curves 1244
- cooling rate 1243
- grain size 1243

Martensite-transformation

- temperature curves**
- effect of austenitizing temperature on slopes of
-1243-1244, 1247
- effect of grain size on slopes of
-1243-1244, 1246

Mechanical properties

- chromium-nickel-molybdenum alloy, 16-25-6
- effect of tempering treatments1042, 1044
- chromium-nickel-molybdenum-manganese alloy ..1041-1046
- effect of cold work ..1045-1046
- effect of quenching temperature1041-1045
- effect of tempering treatments1042-1045
- of molybdenum, control of. See under Molybdenum.
- Super HY-Tuf and SAE 4340 steels1590-1591
- titanium-aluminum-chromium alloys622-634
- titanium-aluminum-molybdenum alloys602-607
- of titanium-molybdenum alloys
- correlation with heat treatment and microstructure
-292-311

Mechanical properties, transverse

- of slack-quenched and tempered wrought steel1331-1358

Mechanical testing

- at low temperatures975-977
- apparatus975-977
- recording diameter gage976-977
- schematic diagram .. 976

Medium carbon steel

See Steel.

Melting point

vanadium1138-1139

Metallographyiron-chromium-molybdenum
alloys802, 804**Microcrack structure**effect of torsional strain..666-680
nature of670-680**Microstrain**

during dynamic loading .. 52-53

Microstructures

alpha-molybdenum die steel
.....1603-1605, 1607-1609
of aluminum stress-rupture
tested at 900 °F 75-81
of annealed tungsten
fractured at various
temperatures400-403
austenitic chromium-nickel
steel960-968
effect of aging time ...963-966
effect of phosphorus
content 965
effect of quenching strains
.....966-968
etchants 961
grain size961-964
photomicrographs
.....962, 964, 966, 968
residual carbide content after
solution treatment ..961-964
of case-hardened boron steel
.....453-454, 466-468
of 16 Cr-25 Ni-6 Mo alloy
during elevated temperature
working1548-1550
chromium-nickel-molybdenum-
manganese alloy ..1046-1051
hot-rolled 1046
effect of cold work 1048-1050
effect of water quenching
from 1800 to 2150 °F
.....1046-1048, 1050
17-25% chromium stainless
steel ..1179, 1183-1190, 1194-
1195, 1197, 1199, 1205-1207
depletion of austenite by
precipitation 1190

Microstructures (cont.)

17-25% chromium stainless steel
growth of austenite into
delta ferrite1194-1195
lamellar carbides in
martensite1197, 1199
residual carbides and
nitrides in martensite
.....1179, 1205-1207
resulting from isothermal
transformation of
austenite1183-1189
of heat treated titanium
alloys574-575, 580
high speed steel
.....736-738, 762, 764-
766, 779-785, 790-792, 795-798
austenite subgrains in
martensite 795
quenched from various
temperatures736-738
subgrain structure
.....782-784, 796-798
of indium arsenic-antimony
alloys391-395
of iron-boron alloys
.....505-507, 511-512, 515
iron-carbon alloys
..978-979, 980, 982, 1323-1327
carbide stringers in ..979, 982
grain size978, 980
of marquenched steels .1507-1510
of molybdenum
during ingot processing
.....1456-1461
of nitrided titanium547-555
of nodular iron 421
relationship to fracture
paths441-443
of plain carbon steels
.....1529-1530, 1533
SAE 1050 steel
.....1228, 1231-1233, 1237-1238
SAE 4340 steel1258-1261
fatigue cracks1258-1261
stainless steel
...1287, 1290-1291, 1293, 1295
Type 309 .1287, 1290-1291, 1295
Type 3101287, 1293-1295
steel834-837
AISI 1340834-837
AISI 2340835, 837
AISI 5140836-837

Microstructures (cont.)

- titanium-aluminum-chromium alloys615-619
- titanium-aluminum-molybdenum alloys597-599
- of titanium-boron alloys .321-325
- of titanium-chromium alloys233-238, 239, 241, 252, 254
- of titanium-molybdenum alloys correlation with heat treatment and mechanical properties292-311
- of titanium-nitrogen alloys317-319
- zirconium hydrogen in646-649
- of zirconium-aluminum alloys359-368

Molybdenum

- in alloy steel effect on transverse properties144-147
- analysis by vacuum-fusion method apparatus376-379 operation of379-380 importance of375-376 nitrogen determinations 383-385 oxygen determinations 380-382 effects of sample oxidation 382 sensitivity of gas-volume measurements 379
- mechanical properties control effect of grain size on ductility1463-1464 effect of rolling temperature 1461 effect of testing temperature1461-1463 factors affecting transition temperature1463-1464 grain growth1454-1455 materials studied 1450 processing ingots 1455 macrostructures during1455-1456 microstructures during1456-1461 tensile properties during1459-1461

Molybdenum (cont.)

- mechanical properties control recrystallization 1451 effect of annealing temperatures ...1452-1453 effect of annealing time 1454 effect of cold work 1452-1453 stress-rupture data at high temperatures122-123

Nickel

- in alloy steel effect on transverse properties144-148 effect on properties of Cu-Ni-Si alloys 331 grain growth time-temperature relationship for1384, 1395 lattice constants702-703 effect of alloying elements702-703 solubility in vanadium ... 1153 stress-rupture data at high temperatures121-122

Nickel alloys

- creep curves703-714 effect of solid solution alloy content on parameter "A" ..708-709, 713 reproducibility703-705 variation of ϵ_0 with solid solution alloy content708-709, 714 variation of slope with solid solution alloy content708-709, 712 creep parameters effect of solid solution alloying elements ...701-714

Nickel-cobalt alloys

- creep curves705-707, 710 creep parameters706-707 creep rates706-708

Nickel-iron alloys

- creep curves705-707, 710 creep parameters706-707 creep rates706-708

Nickel silver

- hardness tempering time-temperature relationship 1380

Nickel-titanium alloys

- creep curves705, 708, 711
- creep parameters706-707
- creep rates706-708

Nickel-tungsten alloys

- creep curves705, 709
- creep parameters706-707
- creep rates706-708

Niobium

- stress-rupture data at high temperatures121, 123

Nitriding

- for surface hardening titanium. See under Titanium.
- in low carbon steel
 - for control of structure with aluminum. See Aluminum nitride in steel.

Nitrogen

- in molybdenum
 - measurement of383-385
- role in graphitization ..1318-1330
- strain energy per atom .. 1114
- use in nitriding titanium .562-563

Nodular iron

- notch ductility
 - Charpy V transition
 - curves422-426
 - comparison with steels422-426
 - effect of silicon and phosphorus423-425
 - significance of427-428
- compositions of irons tested419-420
- drop weight tests
 - effect of alloying elements on fracture temperature431-433
 - effect of microstructure on fracture temperature431-433
 - effect of section size 433-434
- explosion tests435-441
- fracture path vs. microstructure441-443
- microstructures 421
- tensile properties425, 427

Normalizing

- effect on quench cracking of hollow steel cylinders102-103

Notch ductility

- of nodular iron. See Nodular iron.

Notch tensile properties

- effect of notch sharpness on fracture appearance .1018-1019
- specimen1000-1001
- variation of average true stress with sharpness at various strain values1016-1017
- brass1016-1017
- S-8161016-1017
- variation of necking strain with notch sharpness ...1017-1018
- aluminum, 24S-O1017-1018
- brass1017-1018
- copper, annealed1017-1018
- copper, hard drawn .1017-1018
- variation with notch sharpness1006-1010
- aluminum 24S-O 1009
- brass 1007
- copper, annealed 1011
- copper, hard drawn .1006-1008
- S-816 1010
- titanium 1008
- variation of notch strength
 - ratio with notch sharpness1009-1010, 1012-1014
 - fractures determining 1010-1013
 - schematic representation 1014
- variation with unnotch necking strain1013-1015

Notch tensile strength

- effect of notch sharpness1003-1005
- annealed brass1003-1005
- hard drawn copper ..1003-1005

Nucleation and growth

- analysis of proeutectoid ferrite and bainite formation1097-1100
- effect of boron1098-1100

Nucleation rate

- as a function of time ..1097-1100
- effect of boron 1098
- equations1097-1099

Oxygen

- in gray cast iron409-417
- in molybdenum
 - measurement of380-382
- solubility in vanadium ... 1144
- in titanium and zirconium
 - by isotopic method
 - apparatus527-528
 - experimental results ..530-532
 - importance of determining 527

Pearlite spacing

- effect on transition temperatures
 - carbon steels investigated 1528
 - for 0.017% C steel
 -1531, 1534-1535
 - for 0.22% C steel
 -1532, 1534-1535
 - for 0.43% C steel
 -1532, 1534-1535
 - for 0.73% C steel1533-1535
 - for 0.78% C steel1533-1535
 - microstructure of 0.2% C
 - steel1529, 1533
 - microstructure of 0.73% C
 - steel1530, 1533
 - pearlite content of steels
 -1528, 1531-1532
 - related tensile properties
 -1535-1536
 - time-temperature curves
 - for 0.73% C steel....
 -1530, 1533-1534

Phase diagrams

- indium arsenic-antimony 391
- iron-boron501-503
- iron-chromium-molybdenum
 -803, 805
- iron-Fe₃B516-517
- titanium-boron320-324
- titanium-chromium237-238
- titanium-nitrogen314-316
- vanadium-aluminum 1148
- vanadium-carbon 1145
- vanadium-silicon 1150
- vanadium-zirconium ..1156, 1163
- zirconium-aluminum355-358

Phase transformations

- titanium-manganese alloys
 -1058-1061

Phosphorus

- in nodular iron
 - effect on notch ductility
 -423-425
- in SAE 4140-type steels..828-829
- effect on dilation during
 - tempering828-829

Photogram

- Ti-7.72% Mn alloy ...1066, 1068

Photomicrographs

- iron-chromium-molybdenum
 - alloy802, 804
- titanium-manganese alloys
 -1058-1061, 1063

Pin insert specimen

- construction914, 920
- to determine effect of
 - differences in strain during
 - cooling on hardness ...920-921

Plastic deformation

- mechanism of 55

Plastic strain

- delay during dynamic
 - loading 47-52
- mechanism of 55-59

Precipitation hardening

- austenitic chromium-nickel
 - steel948-971
 - effect of aging temperature
 -953, 956-958
 - effect of aging time ...
 -952-954, 957
 - effect of carbon content 952
 - effect of cooling rate from
 - solution temperature 958
 - effect of phosphorus
 - content954-958
 - effect of solution temperature
 -953, 955-956

President's Annual Address 7**Preyield microstrain**

- during dynamic loading .. 52-53

Quench cracking

- of hollow alloy steel cylinders
 - effect of austenitizing
 - temperature101-102

Quench cracking (cont.)

- of hollow alloy steel cylinders
 - effect of boron content 110-111
 - effect of carbon content
 -107, 109-111
 - effect of disk thickness 105-106
 - effect of ingot position 106-109
 - effect of normalizing ..102-103
 - effect of quench temperature
 -103-105
 - effect of wall thickness 103
 - test employed100-101

Quenching

- of nitrided titanium
 - effect on case hardening 559

Quenching constant

- calculation of H values .. 886
- variation of H value887-907
 - in end-quench bars
 -889, 896, 898-900
 - at half-temperature time
 -905-907
 - for two cooling rates
 - and two positions in
 - rounds905-907
 - importance of severity of
 - quench
 -891, 896, 898-899, 901-907
 - within a 2¼-inch round 887, 893
 - with specimen size887-904
 - with temperature887-904

Quench temperature

- effect on quench cracking
 - of hollow steel cylinders
 -103-105

Rare earths

- in alloy steels
 - effect on transverse
 - properties148-153
 - effect on Charpy impact
 - traverses
 -1340-1348, 1351, 1353
 - as a function of distance
 - from the quenched end
 - of end-quenched slabs of
 - steel .1340-1348, 1351, 1353
 - effect of position on
 - transition temperature 1353

Rare earths (cont.)

- effect on tensile property
 - traverses
 - ..1340, 1344-1345, 1347, 1349
 - as a function of distance
 - from the quenched end
 - of end-quenched slabs
 - of steel
 - ..1340, 1344-1345, 1347, 1349

Recrystallization

- of molybdenum
 - in controlling mechanical
 - properties. See under
 - Molybdenum.
 - time-temperature relation-
 - ship for
 - comparison with grain
 - growth .1381, 1388, 1395-1396
 - effect of alloying elements
 -1391-1392
 - equation for 1382
 - importance of grain size
 - control 1377
 - master recrystallization
 - curves1383-1387
 - effect of cold work 1381, 1385
 - theoretical considerations
 -1392-1396
 - with aluminum 1381
 - vanadium, cold-rolled ... 1139

Reduction of area

- transverse of alloy steels
 - effect of composition on. See
 - Transverse mechanical
 - properties.

Retained austenite

- effect on torsion properties 97-98

Rheotropic recovery

- of steel
 - effect of strain aging ..184-196

Rolling temperature

- for molybdenum
 - effect on properties ... 1461

Rotary shadowing853-854**Rupture**

- equation for115-116

Salt bath marquenching

of commercial steels.

See Hardenability test.

Salt baths

corrosive effect on cast Fe-Ni-Cr alloys. See Corrosion resistance.

Secretary's Annual Report.. 16**Sensitivity factor**

in torsion test 97-98

Shear planes

in ferrite single crystals.

See under Single crystals.

Sigma phasein Types 309 and 310 stainless steel1285-1297
formation of1285-1297**Silicon**

in alloy steel

effect on transverse prop-
erties148, 152-153effect on properties of Cu-Ni-Si
alloys 331

in nodular iron

effect on notch ductility.423-425

solubility in vanadium ... 1149

Single crystals

flow and fracture of ferrite

experimental technique

..... 1410-1411

fracture1421-1433

low temperature tests

effect of temperature 1421

tension and compression

..... 1419-1420

mechanical twinning .1434-1435

proposed theory of slip

..... 1407-1408, 1421-1424

atom movements ..1436-1442

compared with experimental

results1421-1423

strength of various planes

..... 1408-1409

room temperature tests

effect of alloy composition

..... 1418

plane of slip 1416

tension vs. compression

..... 1415-1416, 1418-1419

Single crystals (cont.)

flow and fracture of ferrite

shear glide planes....1411-1415

strength of polycrystalline

alloys 1410

yield point1433-1434

Slack quenching

heavy forged steel sections

..... 1331-1358

effect on mechanical prop-

erties1331-1358

Slip

in ferrite single crystals.

See Single crystals.

Solidification

of an ingot1218-1222

probable sequence of events

..... 1218-1222

pasty condition 1222

Solution treatment

of titanium alloys

effect on properties....571-576

Specimens

tension 659

torsion 659

Specimen size

effect on grain growth ..

.....1383, 1385, 1389

Spring alloy

copper-base substitute for

copper-beryllium. See Copper-
nickel-silicon-aluminum alloys.**Stainless steel**intergranular corrosion of ferritic
types

austenite not responsible

..... 214-218

compositions of steels tested

..... 200-201

conditions producing ..197-200

effect of carbon 207

effect of chromium 206

effect of miscellaneous

elements 209

effect of sensitizing heat

treatment211-214

effect of subsequent heat

treatment209-211

Stainless steel (cont.)

- intergran. cor. of ferritic types
 - effect of titanium additions
 - 207-209
 - mechanism of219-222
 - test for determining ...201-202
 - welding tests202-206
- microstructures
 - 1204, 1287, 1290-1291, 1293-1295
 - intergranular precipitate 1204
 - Type 309 .1287, 1290-1291, 1295
 - Type 310.....1287, 1293-1295

Stainless steel, 17-25% chromium

- A₁ temperatures 1179
- austenite decomposition 1182-1183
 - intermetallic compounds
 - associated with ...1182-1183
 - carbide precipitation 1182
 - depletion of austenite by
 - precipitation1190-1191
- high temperature trans-
 - formations1193-1201
 - delta ferrite to aggregate of
 - austenite and carbides
 - 1197-1201
 - mechanism involved
 - 1200-1201
 - invoking delta ferrite.1193-1197
 - growth of austenite into
 - delta ferrite1193-1196
 - substructures1195-1196
 - veining1195-1196
- isothermal austenite transfor-
 - mation..1180-1189, 1191-1193
 - data1180-1182
 - reaction rate curves..1191-1193
 - transformation products
 - 1183-1189
 - effect of transformation
 - temperature1183-1189
 - TTT curves1180-1181
 - martensite reaction 1183
 - microstructures
 - 1179, 1183-1189, 1194-
 - 1195, 1197, 1199, 1205-1207
 - depletion of austenite by
 - precipitation 1190
 - growth of austenite into
 - delta ferrite1194-1195
 - lamellar carbides in mar-
 - tensite1197, 1199

Stainless steel, 17-25% Cr (cont.)

- microstructures
 - residual carbides and nitrides
 - in martensite.1179, 1205-1207
 - resulting from isothermal
 - transformation of austenite
 - 1183-1189
 - transformation of austenite by
 - growth of existing delta
 - ferrite1191-1193

Stainless steel, ferritic

- high temperature trans-
 - formations1176-1213

Stainless steel, Types 309 and 310

- formation of sigma phase
 - 1285-1297
- aging treatments 1286
- diffraction studies 1289
- ferromagnetic permeability
 - tests1288-1289
- hardness1288, 1292
 - effect of aging treatments
 - 1288, 1292
- Izod impact1288, 1292
 - effect of aging treatments
 - 1288, 1292
 - relation to microstructure 1292
- X-ray analysis of needle
 - constituent 1297

Stainless steel, Types 430 and 442

- corrosion1204-1205
 - effect of welding and post-
 - weld annealing1204-1205
- tensile properties1204-1205
 - effect of welding and post-
 - weld annealing1204-1205

Statistical analyses

- of the stress-rupture test.
 - See Stress-rupture test.

Steel

- case-carburized
 - effect of boron on hardenability.
 - See under Hardenability.
- critical temperatures ..1270-1284
 - elevation by high heating
 - rates1270-1284
 - apparatus for deter-
 - mining1271-1274
 - method of determining
 - 1272-1274

Steel (cont.)

- effect of boron1089-1135
 - adsorption effects ...1091-1093
 - temperature dependence
 - 1092-1093, 1123-1124
 - thermodynamic conditions
 - leading to1091-1092
 - on diffusivity of carbon
 - in austenite 1095
 - grain boundary effect.1090-1093
- effect of type and amount of nonmartensitic decomposition products on lowest temperature for ductile fracture .
 - 842, 844
- impact energy as a function
 - of decomposition temperature841, 843
 - effect of decomposition products841, 843
- impact energy vs. temperature837-843
 - effect of decomposition products837-843
- influence of nonmartensitic decomposition products on true stress-true strain relationships843-845
- isothermal transformation characteristics 1562
- isothermal transformation kinetics1096-1100
 - effect of boron1096-1097
- microstructures833-837
- pearlite spacing effect on transition temperatures.
 - See Pearlite spacing.
- quenched and tempered ..830-846
 - effect of nonmartensite decomposition products on properties830-846
- temperatures for 10 and 30% transformation during cooling to various isotherms.833-837
- temper brittleness1298-1317
 - effect of chemical composition on susceptibility
 - 1298-1317
 - SAE 3312 ..1299-1300, 1302-1304
- tempered
 - carbide phases in869-871

Steel (cont.)

- tensile properties843-845
 - effect of nonmartensitic decomposition products
 - 843-845
- transverse mechanical properties1331-1358
 - of slack-quenched and tempered wrought steel..
 - 1331-1358

Steel, hypoeutectoid

- embryo concentrations for solution behavior ..1093-1094
- schematic diagram 1094

Steel, medium carbon

- changes in magnetization vs. temperature813-817
- effect of silicon813-816
 - with different retained austenite contents 815
- electron micrographs824-825
- length changes on tempering
 - 817-822
 - for 100% austenite820-822
 - activation energies ..820-821
 - effect of silicon..... 821
 - for 100% martensite ...817-820
 - activation energies .. 820
 - effect of silicon content
 - 817-820
 - rate equation 820
- tempering812-827
 - effect of silicon.....812-827

Steel, trade designation

- 4170 type
 - hardenability 1127
 - effect of austenitizing temperature 1127
 - effect of boron 1127
- 81B40
 - hardenability curves
 - effect of quenching temperature1126-1127
- NE 9440
 - hardenability1505-1509
- NE 98V65
 - hardenability1505-1509
- S-816
 - notch tensile properties
 - 1010, 1016-1017

Steel, trade designation (cont.)

- S-816
 - notch tensile properties
 - variation of average true stress with sharpness at various strain values 1016-1017
 - variation with notch sharpness 1010
- SAE 1050
 - martensite transformation 1225-1253
 - influence of heat treating variables 1225-1253
 - microstructure 1228, 1231-1233, 1237-1238
- SAE 1095
 - hardenability 1505-1509
- SAE 1335
 - hardenability 1505-1509
- SAE 1340
 - rheotropic recovery and strain aging behavior 184-196
- SAE 2340
 - hardenability 1505-1509
- SAE 3140
 - hardenability 1505-1509, 1513-1515
 - temper brittleness 1304
- SAE 3312
 - impact energy 1299-1300, 1302-1304
 - at various testing temperatures 1299-1300, 1302-1304
 - effect of cooling rate 1299-1300, 1302-1304
- SAE 4140
 - hardenability 1505-1509
- SAE 4340
 - fatigue strength 1254-1269
 - effect of inclusions 1254-1269
 - hardenability 1505-1509
 - tensile properties 1265-1269
 - effect of torsional pre-strain upon 1265-1269
- SAE 6150
 - hardenability 1505-1510
- TS 8117
 - dilatometric cooling curves 1121-1123
 - effect of boron content 1121-1123

Strain aging

- of 16 Cr - 25 Ni - 6 Mo alloy 1547
- effect on rheotropically embrittled steel 184-196

Strain energy

- in interstitial solid solutions 1112-1116
- as a function of the distance from the solute atom 1114-1116
- diameter of interstitial atoms 1112-1113
- boron 1113
- carbon 1113
- equations 1112
- nitrogen 1113
- equations 1114
- peaks 1115-1116
- per atom 1114

Strain hardening

- apparent rate 989
- exponent of 989
- measurement of 985-988

Strain hardening exponent

- definition 987
- iron-carbon alloys 989-991
- effect of carbon content 990
- effect of ferrite grain size 990-991
- effect of temperature 989-991

Strain rate

- effect on proportional limit and ultimate strength 46-47
- vs. time 45

Stress-rupture data

- correlation for metals at high temperatures
 - aluminum data 117-119
 - of atomic numbers with activation energies for creep, rupture and self-diffusion 125-127
 - beryllium data 119-121
 - commercial alloy data 122-125
 - equation for total creep 113-115
 - molybdenum data 122-123
 - nickel data 121-122
 - niobium data 121, 123
 - rupture equation 115-116
 - titanium data 119-121

Stress-rupture tests

- a statistical analysis for 2S
 - aluminum at 900 °F.. 63-86
 - experimental results ... 66-68
 - microstructures 75-81
 - statistical treatment ..
 - 69-74, 79-85
 - test method 65-66
 - uniformity of material . 68-69

**Stress-rupture tests,
high temperature**

- brass, alpha
 - ...1023, 1026, 1031-1032, 1035
- effect of grain size
 - 1023, 1026, 1031-1032, 1035
- on minimum creep rate at
 - various temperatures and
 - stresses ...1031-1032, 1035
- on rupture life at various
 - temperatures and
 - stresses1023, 1026

Stress-strain curves

- aluminum
 -684-686, 689-691, 695-696
- comparison of effects of
 - recovery and stress
 - recovery695-696
- effect of creep straining.684-686
- prestrained at various
 - temperatures689-691
- aluminum-copper alloys .
 - 1078-1081
- effect of CuAl_2 content
 - and size1078-1081
- for Al-Zn-Cu alloys 350
- for 16 Cr-25 Ni-6 Mo alloy
 - at elevated temperatures
 - 1546-1548
- copper, cold-worked667-668
- relation to flow direction
 - 667-668
- iron-carbon alloy985-987
- effect of testing tem-
 - perature985-987
- notch and unnotch bars.1003-1005
- various materials and con-
 - ditions1002-1004

Stress-strain relations

- under dynamic loading ... 38-42

Structure

- of low carbon steel
 - effect of aluminum nitride on.
 - See Aluminum nitride in steel.
- of steels marquenched in salt
 - and water 1506

Subboundary

- definition 854

Subboundary carbide precipitation

- in iron-carbon alloys 867
- first stage of tempering.867-869
- third stage of tempering.869-875
- nature of carbide869-871
- nature of reaction ...871-874
- relationship to embrittle-
 - ment874-875

Subgrain

- definition 854

Supercooling

- in alloys1214-1222
- constitutional supercooling
 - 1217-1218

Surface hardening

- of titanium by nitriding.
 - See under Titanium.

Surface heat abstraction

- coefficient899, 903

**Technical Program and Reports
of Officers, American Society
for Metals—35th Annual Con-
vention, Cleveland, October
19 to 23, 1953 1****Temper brittleness. See also**

- Temper embrittlement.
- of boron steel. See under
 - Boron steel.
- nature of1305, 1307
- precipitating phase..1305, 1307
- steels1298-1317
- effect of carbon 1307
- effect of chemical composition
 - on susceptibility ..1298-1317
- effect of chromium 1309
- effect of manganese..1308-1309
- effect of nickel1307-1308
- effect of phosphorus .. 1309

Temper embrittlement. See also

- Temper brittleness.
- iron-carbon alloys 1305
- iron-carbon-chromium alloys 1306
- iron-carbon-chromium-manganese alloys 1306
- iron-carbon-chromium-nickel alloys 1306
- iron-carbon-chromium-nickel-manganese alloys 1308
- iron-carbon-manganese alloys 1305
- iron-carbon-nickel alloys. 1305
- iron-carbon-nickel-manganese alloys 1308
- SAE 3140 steel 1304
- SAE 3312 steel
 - effect of carbon 1304
 - effect of chromium 1304
 - effect of constituents .. 1304
 - effect of nitrogen 1304
- test for1299-1301

Tempering

- iron-carbon alloys851-881
 - microstructural changes on851-881
- medium carbon steels ...812-827
 - effect of silicon on kinetics of812-827
 - length changes817-822
 - effect of silicon817-822
- SAE 4140-type steels ...828-829
 - dilation during828-829
 - effect of aluminum ..828-829
 - effect of phosphorus .828-829
- time and temperature vs. hardness1378-1381

Tensile fracture

- appearance663-665
 - effect of torsional prestrain663-665
- fracture angle663-665
 - variation with torsional prestrain663-665
- helical fracture pattern ..664-665
- microcrack structure666-680
 - effect of torsional strain.666-672

Tensile fracture stress

- copper661-666
 - effect of torsional pre-strain661-666

Tensile properties

- aluminum681-699
 - effect of prestrain histories681-699
 - effect of stress recovery.691-699
- effect of nonmartensitic decomposition products ..843-845
- of high strength titanium alloys
 - effect of heat treatment on571-585
- stainless steel, Type 430 and Type 4421204-1205
 - effect of welding and post-weld annealing1204-1205
- titanium-aluminum-chromium alloys622-634
 - effect of composition .. 622
 - effect of heat treatment.622-634
- titanium-aluminum-molybdenum alloys ..602-607
 - effect of composition...602-607
 - effect of cooling rate from beta solution temperature.602-607

Tensile property traverses

- as a function of distance from the quenched end of end-quenched slabs of steel 1338-1344
 - corrected to a constant tensile strength 1338-1339, 1343-1351
- yield strength-tensile strength ratio1338-1340

Tensile strength

- transverse of alloy steels
 - effect of composition on. See Transverse mechanical properties.

Tensile stress

- effect on critical temperatures1279-1281

Tension-impact properties

- static vs. dynamic 42-43
- critical impact velocity. 43-44

Thermal analysis

- of indium arsenic-antimony alloys390-391

Thermal diffusivity value ..904-905

Thermocouple wires

- insulation required in quench bath1233-1235
- cooling curves 1234

Time-temperature transformation

- titanium-aluminum-chromium alloys613-620
 - effect of composition on.613-620
 - effect of heat treatment.613-619
- titanium-aluminum-molybdenum alloys595-598
 - effect of composition on.595-598
 - effect of heat treatment.595-598

Tin

- effect on properties of Cu-Ni-Si alloys336-337

Titanium

- additions to ferritic stainless steels
 - effect on intergranular corrosion207-209
- effect on properties of Cu-Ni-Si alloys335-336
- notch tensile properties .. 1008
 - variation with notch sharpness 1008
- oxygen content
 - measurement by isotopic method. See under Oxygen.
- stress-rupture data at high temperatures119-121
- surface hardening
 - alloys tested 257
 - gas carburizing267-270
 - induction heat treatment 270-273
 - liquid carburizing264-267
 - need for 257
 - pack carburizing with lampblack 264
 - pack carburizing with steel carburizer259-264
 - wear test258-261
- surface hardening by ammonia nitriding
 - effect of ammonia flow rate on543-546
 - effect of time-temperature variables546-557
 - equipment and procedure 541-543

Titanium (cont.)

- surface hardening by ammonia nitriding
 - importance of 540
 - mechanism of nitriding.561-563
 - comparison with nitrogen nitriding562-563
- microstructures547-555
- nature of case and core.557-561
 - effect of quenching on 559
- electrical resistivity measurements559-560
- X-ray diffraction study 557-559

Titanium alloys

- heat treatment of high strength alloys
 - age hardening effects on properties576-584
 - microstructures576-580
- alloys tested570-571
- review of alloy development569-570
- solution treatment effects
 - on properties571-576
 - microstructures574-575
- stability of overaged alloys at high temperatures.584-585

Titanium-aluminum-chromium alloys

- age hardening ...620-622, 637-638
- effect of chromium620-622
- Charpy impact623-634
- effect of composition...623-634
- effect of forging practice 627-628
- effect of heat treatment.623-634
- hardenability611-613
- effect of composition ..611-613
- hardness611-615, 619-620, 623-625, 630-639
- heat treatment622-634
- effect on mechanical properties622-634
- mechanical properties ...622-634
- microstructures615-619
- tensile properties622-634
- effect of composition ..622-634
- effect of heat treatment.622-634
- TTT determinations613-620
- effect of composition ..613-620
- effect of heat treatment.613-619

Titanium-aluminum-molybdenum alloys

- age hardening600-604
- effect of composition ..600-602
- Charpy impact602-607
- effect of composition ..602-607
- effect of cooling rate from beta solution temperature.602-607
- effect of forging practice 606
- hardenability592-595
- effect of composition on.594-595
- procedure592-593
- hardness.....600, 602, 605-606
- heat treating 593
- mechanical properties602-607
- microstructures597-599
- preparation of591-592
- tensile properties602-607
- effect of composition ..602-607
- effect of cooling rate from beta solution temperature.602-607
- TTT determinations595-598
- effect of composition on.595-598
- effect of heat treatment.595-598

Titanium-boron system

- microstructures321-325
- phase diagram320-324
- X-ray diffraction results..324-326

Titanium-chromium alloys

- hardness 1069
- isothermal transformation
 - eutectoid temperature . 233
 - phase diagram237-238
 - Ti-2.35% Cr alloy240-243
 - hardness vs. transforma-
tion time 244
 - microstructure 241
 - M_s temperature 240
 - TTT diagram 244
 - X-ray diffraction study
..... 240-243
 - Ti-4.64% Cr alloy238-240
 - hardness vs. transforma-
tion time 242
 - microstructure239, 241
 - M_s temperature238-239
 - TTT diagram 242
 - X-ray diffraction study
..... 239-240
 - Ti-5% Cr alloy
 - TTT diagram 252

Titanium-chromium alloys (cont.)

- isothermal transformation
 - Ti-7% Cr alloy
 - TTT diagram 252
 - Ti-7.54% Cr alloy
 - electron microscope
studies243-248
 - hardness vs. transformation
temperature238-239
 - mechanism of hardening
..... 247-249
 - microstructure233-238
 - TTT diagram 238
 - X-ray diffraction study
.....235-238
 - Ti-9% Cr alloy
 - microstructure252, 254
 - TTT diagram 253
 - Ti-17% Cr alloy
 - TTT diagram 253
 - X-ray diffraction 1069

Titanium-chromium system

- hardness588-591
- effect of composition on.588-591

Titanium-iron alloys

- hardness 1069
- X-ray diffraction 1069

Titanium-manganese alloys

- eutectoid-temperature deter-
mination 1058
- hardness vs. time for isothermally
transformed specimens
.....1061-1062, 1066, 1068
- RC-130A alloy 1073
- Ti-2.91% Mn alloy....
..... 1061-1062, 1065
- Ti-7.72% Mn alloy.1062, 1066
- Ti-12.3% Mn alloy.1062, 1068
- isothermal transformation
..... 1056-1074
- diagram ..1059-1062, 1065, 1072
 - Ti-2.91% Mn alloy.1059-1060
 - Ti-7.72% Mn alloy..
..... 1061-1062, 1072
 - Ti-12.3% Mn alloy.1061, 1065
- omega phase1065-1070
- X-ray diffraction1065-1070
- phase transformations..1058-1061
- photomicrographs .1058-1061, 1063
- X-ray diffraction1062-1070

Titanium-molybdenum alloys

- hardness 1069
- study of response to heat treatments
 - correlation of mechanical properties with microstructure 301-308
- impact strength of isothermally transformed alloys 297-299
- impact strength of quenched and reheated alloys .. 300-303
- tensile properties of isothermally transformed alloys 294-297
- tensile properties of quenched and reheated alloys . 297-298
- TTT diagrams . 294-295, 298-299
- X-ray diffraction 1069

Titanium-molybdenum system

- hardness 588-590
- effect of composition on 588-590

Titanium-nitrogen system

- microstructures 317-319
- nitrogen losses 316-317
- phase diagram 314-316
- X-ray diffraction results . 319-320

Tool steel

- angular-appearing carbides
 - in 716-725
- effect of heat treat temperature and time 719-724
- electrolytic extraction of 718-719
- electron microscopy of 719, 721-724
- nature of 723-725
- parameters of 724-725
- photomicrographs . 720-721, 723

Torsion test

- factors controlling strength in 95-99
- appearance of fractures 92-97
- sensitivity factor 97-98
- test method 88-89
- torsion properties 89-92

Transformation kinetics, isothermal

- Mn-Cr-Si steel 1096-1098
- effect of boron on ... 1096-1098

Transformations

- sources of shear in 1116-1117

Transition temperatures

- for boron steels 485, 487
- effect of pearlite spacing of steel on, See Pearlite spacing.
- iron-carbon alloys 1305
- iron-carbon-chromium alloys 1306
- iron-carbon-chromium-manganese alloys 1306
- iron-carbon-chromium-nickel alloys 1306
- iron-carbon-chromium-nickel-manganese alloys 1308
- iron-carbon-manganese alloys 1305
- iron-carbon-nickel alloys 1305
- iron-carbon-nickel-manganese alloys 1308
- in iron-vanadium system 278-283
- in iron-vanadium-titanium system 283-288
- for molybdenum
 - factors affecting 1463-1464
- of nodular iron 422-443
- SAE 3312 steel 1302-1303
- effect of temper embrittlement 1303
- steel
 - effect of carbon 1307
 - effect of chromium 1309
 - effect of manganese ... 1309
 - effect of nickel 1307-1308

Transverse mechanical properties

- of alloy steels
 - effect of boron 138-144
 - effect of carbon 135-139
 - effect of chromium ... 144-147
 - effect of molybdenum . 144-147
 - effect of nickel 144-148
 - effect of rare earths ... 148-151
 - in combination with boron and silicon 151-153
 - effect of silicon 148
 - effect of vanadium 148
 - hardenability 131-135

Treasurer's Annual Report 11**TTT curves**

- 17-25% chromium stainless steel 1180-1182

TTT diagrams

- of RC-130A alloy 1072
- of titanium-chromium alloys
 - containing 2.35% Cr ... 244
 - containing 4.64% Cr ... 242
 - containing 5% Cr 252
 - containing 7% Cr 252
 - containing 7.54% Cr ... 238
 - containing 9% Cr 253
 - containing 17% Cr 253
- Ti-2.91% Mn alloy ...1059-1060
- Ti-7.72% Mn alloy
 -1061-1062, 1072
- Ti-12.3% Mn alloy ...1061, 1065

Tungsten, annealed

- flow and fracture characteristics
 - ductile-to-brittle transition
 - temperatures399-400
 - factors affecting404-407
 - effect of temperature on
 -404-405
 - flow curves403-404
 - microstructures400-403
 - tensile properties at various
 - temperatures399-400
 - types of brittleness ... 405

Twinning

- in ferrite single crystals. See under Single crystals.

Vacuum-fusion analysis

- of oxygen and nitrogen in molybdenum. See under Molybdenum.
- of oxygen in gray cast iron
 -414-415

Vanadium

- in alloy steel
 - effect on transverse
 - properties 148
- cold-rolled 1139
- recrystallization temperature
 - 1139
- hardness 1139
- melting point1138-1139
- solubility of aluminum in 1145
- solubility of copper in ... 1155
- solubility of nickel in 1153
- solubility of oxygen in .. 1144
- solubility of silicon in ... 1149
- solubility of zirconium in 1155

Vanadium-aluminum system

-1145-1149
- intermediate phases ...1145-1148
- lattice parameters ..1146, 1148
- peritectic temperatures
 -1145, 1147
- phase diagram 1148
- microstructures 1149

Vanadium-beryllium system

-1139-1141
- eutectic composition 1140
- eutectic temperature 1140
- intermediate phase VBe₂
 -1139-1140
- microstructure V-5% Be
 - alloy1140-1141

Vanadium binary systems

-1136-1167
- microstructures 1138
- V-1% Ti 1138

Vanadium-boron system 1140-1141

- eutectic temperature 1140
- intermediate phases 1140
- lattice parameters 1140
- microstructures1140-1141

Vanadium-carbon system

-1140-1143, 1145
- eutectic composition 1142
- eutectic temperature 1142
- intermediate phases ...1140-1141
- microstructures1142-1143
- phase diagram 1145

Vanadium-chromium system

-1150-1151

Vanadium-cobalt system 1152-1153

- intermediate phases ...1152-1153

Vanadium-columbium system 1155

- microstructure1157-1158

Vanadium-copper system

-1151, 1155

Vanadium-iron system 1152**Vanadium-manganese system**

-1151-1152
- intermediate phases 1152

Vanadium-molybdenum system

.....	1157-1158
microstructure	1158

Vanadium-nickel system

.....	1151, 1153-1154
intermediate phases ...	1153-1154
lattice parameters ...	1153-1154
microstructure	1151, 1154
V ₃ Ni phase	1153-1154

Vanadium-nitrogen system

.....	1142-1143, 1147
intermediate phases	1142
lattice constants	1143
VN phase	
melting point	1142
V ₂ N phase	
lattice parameters ...	1142
microstructures ..	1142-1143, 1147

Vanadium-oxygen system

.....	1144-1147
intermediate phases ...	1144-1146
lattice parameters ...	1144-1146
VO phase	1145
microstructures	1144, 1147

Vanadium-silicon system

1148-1151	
eutectic composition	1149
eutectic temperature	1149
intermediate phases ...	1148-1151
microstructure	1150-1151
phase diagram	1150

Vanadium-silver system

...	1157
-----	------

Vanadium-tantalum system

.....	1157-1159
microstructures	1158
V-Ta sigma phase	1158-1159
lattice parameters	1159

Vanadium-tin system

.....	1157
-------	------

Vanadium-titanium system

1150	
------	--

Vanadium-tungsten system

.....	1159-1160
-------	-----------

Vanadium-zirconium system

.....	1155-1156, 1163-1164
eutectic temperature	1155
intermediate phase	1155
peritectic temperature ...	1155
phase diagram	1156, 1163
microstructures	1156

Volumetric mean free path

.....	1076-1077
equation	1076

Wear test

for surface-hardened	
titanium	258-261

Work softening

of Timken alloy 16-25-6 at	
elevated temperatures	
constant strain rate tests	
.....	1544-1545
interrupted tension test	
.....	1546-1547
strain aging during ..	1547
mechanism of	1550-1552
microstructural changes	
.....	1548-1550
true stress - true strain	
curves	1546-1548

X-ray diffraction

bainitic structures	1579
iron-chromium-molybdenum	
alloys	801-802
Chi phase	801-802
"N" phase	802
martensitic structures ..	1575-1579
carbides detected in residues	
.....	1578-1580
SAE 2340 steel	1579
SAE 4330 steel	1580
SAE 4340 steel	1580
effect of tempering	
temperature	1575-1576
graphical representation	
of patterns of carbide	
residues from SAE 2340	
steel	1576-1577
effect of tempering time	
.....	1576-1577
graphical representation	
of patterns of carbide	
residues from SAE 4330	
steel	1576, 1578
time-temperature relation-	
ships	1577-1579
photogram	1066, 1068
Ti-7.72% Mn alloy ..	1066, 1068
titanium-chromium alloy	1069
titanium-iron alloys	1069

X-ray diffraction (cont.)

- titanium-manganese alloys
.....1062-1070
- analysis of patterns ... 1067
- isothermally transformed
.....1062-1070
- omega phase1065-1070
- titanium-molybdenum alloy 1069

X-ray diffraction study

- of aluminum stress-
rupture tested at 900 °F 77-81
- of indium arsenic-antimony
alloys392-396
- of nitrided titanium557-559
- of titanium-boron alloys..324-326
- of titanium-chromium alloys
.....235-243
- of titanium-nitrogen alloys
.....319-320
- of zirconium-aluminum alloys 369

X-ray photograms

- aluminum
....683-685, 688-690, 692-694
- at various creep strains 683-685
- prestrained and stress-
recovered to various
strains692-694
- prestrained at various
temperatures688-690
- aluminum-copper alloys.1083-1084
- fractured specimens 1083-1084
- effect of test temperature
.....1083-1084

Zirconium

- grain growth
time-temperature relation-
ship for1387, 1395
- hardness
tempering time-temperature
relationship 1379
- hydride phase
.....640-642, 644, 646-654
- diffraction pattern652-653
- identification649-654
- hydrogen in640-649
- diffusion rates 644
- effect on ductility640-642
- equilibrium pressure ..644-646
- microstructures646-649
- solubility642-644
- oxygen content
measurement by isotopic
method. See under Oxygen.
- solubility in vanadium ... 1155

Zirconium-aluminum system

- aluminum-rich alloys 369
- melting range determinations 369
- phase diagram355-358
- phase relationships with
intermediate aluminum
contents361-369
- microstructures362-368
- X-ray diffraction study 369
- zirconium-rich alloys357-361
- microstructures359-362